



## **5/8" SPIRAL BALANCE MADE FOR NON-TILT RESIDENTIAL & COMMERCIAL WINDOWS.**

**SMOOTH, UNIFORM OPERATING FORCE**  
*THIS TECHNOLOGY PROVIDES CONSISTENT, UNIFORM  
OPERATION THROUGHOUT THE FULL TRAVEL RANGE OF THE  
SASH*

**BROAD ADJUSTABLE WEIGHT RANGES**  
*REDUCE INVENTORY REQUIREMENTS  
FINE TUNE WINDOW PERFORMANCE  
FIELD ADJUSTABLE*

**PERFORMANCE TO AAMA CLASS 2**  
*BALANCE PROVIDES A MINIMUM OF 40% LIFT ASSISTANCE*

**SPRINGS BY CALDWELL**  
*DELIVERS HIGH QUALITY, CONSISTENT  
PERFORMANCE*

**LASER WELDED ALUMINUM TUBES**  
*PROVIDE STRUCTURAL STRENGTH AND DURABILITY*

**WIDE RANGE OF HARDWARE OPTIONS  
FOR SASH ATTACHMENT**  
*COMPATIBLE WITH A WIDE VARIETY OF  
CALDWELL BRACKETS AND CLIPS  
EASILY UTILIZED IN ALUMINUM AND WOOD  
WINDOW APPLICATIONS*



**WEIGHT RANGES: 4 - 40 LBS  
LENGTHS: 7 - 51 INCHES  
AAMA 902-07 CLASS 2  
VERIFIED COMPONENT**



MAXIMUM EXTENDED LENGTH = 2 X TUBE LENGTH  
 MINIMUM RETRACTED LENGTH = TUBE LENGTH + 1 1/8"

## SPIREX® WEIGHT CAPACITY CHART

TUBE LENGTH (INCHES)	SASH WEIGHTS SUPPORTED (LBS)
7	4 - 24
8	4 - 25
9 - 14	4 - 26
15 - 16	4 - 28
17	4 - 40
18 - 22	6 - 40
23 - 32	7 - 40
33 - 45	12 - 40
46 - 47	14 - 40
48 - 49	16 - 40
50 - 51	18 - 40

### HOW TO ORDER:

1. Determine your sash weight and tube length needed
2. Consult with Customer Service for tensioning charts and further ordering instructions.